

RESERVE STUDIES | INSURANCE APPRAISALS | WIND MITIGATION



Windstorm Mitigation Report (OIR-B1-1802)

Raintree Village Condominium, Inc. 2101 Sunset Point Rd, Units 1701-1702 Clearwater, FL 33765

Prepared Exclusively for Raintree Village Condominium, Inc.

As of 9/9/2021 | FPAT File# MUD2014600



Felten Property Assessment Team

RECAPITULATION OF MITIGATION FEATURES For 2101 Sunset Point Rd, Units 1701-1702

1. Building Code: Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1973 per Pinellas County

Property Appraiser.

2. Roof Covering: FBC Equivalent

Comments: The roof covering was replaced in 2015. The roof permit was

confirmed and the permit number is BCP2015-12331. This roof was verified as meeting the building code requirements outlined on the

mitigation affidavit.

3. Roof Deck Attachment: Level C

Comments: Inspection verified 1/2" plywood roof deck attached with 8d nails at a

minimum 6" on the edge & 6" in the field.

4. Roof to Wall Clips

Attachment:

Comments: Inspection verified hurricane clips fastened with a minimum of three

nails.

5. Roof Geometry: Other Roof

Comments: Inspection verified a gable roof shape.

6. SWR: Yes

Comments: SWR was verified at time of inspection. The Secondary Water

Resistance verified is a self-adhering peel and stick.

7. Opening Protection: None or Some Glazed Openings

Comments: No opening protection verified at the time of inspection.

Address Verification



Exterior Elevation



Roof Construction



Roof Construction



Roof Construction







SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 2101 Sunset Point Rd, Units 1701-1702

FPAT File #MUD2014600

Roof Construction



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 9/9/2021	•	-
Owner Information		
Owner Name: Raintree Village Cond	Contact Person: Robert Kelly	
Address: 2101 Sunset Point Rd, Un	Home Phone:	
City: Clearwater	Zip: 33765	Work Phone: (727) 726-8000
County: Pinellas		Cell Phone:
Insurance Company:		Policy #:
Year of Home: 1973	# of Stories: 2	Email:

msarance company.	pany.						
Year of Home: 1973	# of Stories:	2	Email:	Email:			
NOTE: Any documentation used in vaccompany this form. At least one phthough 7. The insurer may ask additional transfer of the control of the	otograph must ac	company this form	ı to validate each attribute m	narked in questions 3			
 Building Code: Was the structure to the HVHZ (Miami-Dade or Broward) A. Built in compliance with the FBC 3/1/2002: Building Permit Appl B. For the HVHZ Only: Built in comprovide a permit application with [X] C. Unknown or does not meet the result. 	d counties), South F : Year Built . For ication Date (MM/DD/ pliance with the SF h a date after 9/1/1	Florida Building Co homes built in 2002 YYYY) FBC-94: Year Built 994: Building Perm	de (SFBC-94)? 2/2003 provide a permit application For homes built in 1	994, 1995, and 1996			
2. Roof Covering: Select all roof covering OR Year of Original Installation/Recovering identified.				mpliance for each roof			
2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance			
 [X] 1. Asphalt/Fiberglass Shingle [] 2. Concrete/Clay Tile [] 3. Metal [] 4. Built Up [] 5. Membrane [] 6. Other 	12/15/2015			0 0 0 0 0			
 [X] A. All roof coverings listed above installation OR have a roofing [] B. All roof coverings have a Miamipermit application after 9/1/19 [] C. One or more roof coverings do not D. No roof coverings meet the requirement. 3. Roof Deck Attachment: What is the 	permit application Dade Product App. 94 and before 3/1/2 of meet the requirer rements of Answer	date on or after 3/1, roval listing current 002 OR the roof is ments of Answer "A" or "B".	02 OR the roof is original and at time of installation OR (for original and built in 1997 or la " or "B".	built in 2004 or later. the HVHZ only) a roofing			
[] A. Plywood/Oriented strand board (staples or 6d nails spaced at 6" a -OR- Any system of screws, na uplift less than that required for [] B. Plywood/OSB roof sheathing w 24"inches o.c.) by 8d common other deck fastening system or t	OSB) roof sheathin long the edge and 1 tils, adhesives, othe Options B or C bel ith a minimum thinails spaced a maximal	ng attached to the re 2" in the fieldOR- er deck fastening sy low. ckness of 7/16"included further factors.	oof truss/rafter (spaced a maxing Batten decking supporting wo system or truss/rafter spacing the attached to the roof truss/rafter in the fieldOR- Any system	od shakes or wood shingles nat has an equivalent mean fter (spaced a maximum o of screws, nails, adhesives			

- a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [X] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 1701-1702, Clearwater

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

	or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.
	D. Reinforced Concrete Roof Deck.
	E. Other: F. Unknown or unidentified.
	G. No attic access.
4.	Roof to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within 5 feet of the inside or outside corner of the roof in determination of WEAKEST type)
	A. Toe Nails [I] Transforfer and and to tangeless of well using noils driven at an angle through the transform and attached to the
	[] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or [] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are:
	[X]Secured to truss/rafter with a minimum of three (3) nails, and [X]Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe
ΓX	corrosion. B. Clips
ľ	[X] Metal connectors that do not wrap over the top of the truss/rafter, or
	[] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
[]	C. Single Wraps
	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
[]	D. Double Wraps
	[] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
	E. Structural Anchor bolts structurally connected or reinforced concrete roof.
[]	F. Other: G. Unknown or unidentified H. No attic access
5.	Roof Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[]	A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter:
[]	B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
[X	C. Other Roof Any roof that does not qualify as either (A) or (B) above.
[X []	Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR.
[]	C. Unknown or undetermined.

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 1701-1702, Clearwater

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed O	Non-Glazed Openings			
openi form	an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		Х	Х	Х		Х
A Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	B Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	C Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	Χ				Х	

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115
 - [] A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
 - A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
 - [] A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- [] B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 - B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 - B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
- [] <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
 - C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
 - C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
 - C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials	ff	Property	Address	2101	Sunset Poin	t Rd	Units	1701-1702	Clearwater
inspectors initials _		_rroperty	ruui css	2101	Dunset I om	t Itu,	Omto	1/01 1/02,	Cicai water

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

[] N. Exterior Opening Protection (unverified shutter systems with no documentation) All Glazed openings are protected with protective coverings not meeting the requirements of Answer "A", "B", or C" or systems that appear to meet Answer "A" or "B" with no documentation of compliance (Level N in the table above).

N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist

N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the table above

N.3 One or More Non-Glazed openings is classified as Level X in the table above

[X] X. None or Some Glazed Openings One or more Glazed openings classified and Level X in the table above.

MITIGATION INSPECTIONS MUST BE CERTIFIED BY A QUALIFIED INSPECTOR. Section 627.711(2), Florida Statutes, provides a listing of individuals who may sign this form.						
Qualified Inspector Name: John Felten	License Type: CBC <u>License or Certificate #:</u> CBC1255984					
Inspection Company: Felten Property Assessment Team			866-568-7853			

Qualified Inspector – I hold an active license as a: (check one)

Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam.

Building code inspector certified under Section 468.607, Florida Statutes.

General, building or residential contractor licensed under Section 489.111, Florida Statutes.

Professional engineer licensed under Section 471.015, Florida Statutes.

Professional architect licensed under Section 481.213, Florida Statutes.

Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.

Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed
under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons.
Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and
experience to conduct a mitigation verification inspection.
I, <u>John Felten</u> am a qualified inspector and I personally performed the inspection or (<i>licensed contractors and professional engineers only</i>) I had my employee (<u>Ian Wright</u>) perform the inspection and I agree to be responsible for his/her work.
Qualified Inspector Signature:Date: 9/9/2021
Qualified Inspector Signature: Date: 9/9/2021
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form
is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the
appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who
certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally

Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative.

Signature:

Date:

An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)

The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 1701-1702, Clearwater

performed the inspection.

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.