

RESERVE STUDIES | INSURANCE APPRAISALS | WIND MITIGATION



Prepared Exclusively for Raintree Village Condominium, Inc.

As of 11-25-2020 | FPAT File# MUD2015282

Felten Property Assessment Team

866.568.7853 | www.fpat.com



RECAPITULATION OF MITIGATION FEATURES For 2101 Sunset Point Rd, Units 2401-2402

1. Building Code: Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1973 per Pinellas County

Property Appraiser.

2. Roof Covering: FBC Equivalent

Comments: The roof covering was replaced in 2020. The roof permit was

confirmed and the permit number is BCP2020-070709. This roof was verified as meeting the building code requirements outlined on the

mitigation affidavit.

3. Roof Deck Attachment: Level C

Comments: Inspection verified 1/2" plywood roof deck attached with 8d nails at a

minimum 6" on the edge & 6" in the field.

4. Roof to Wall Clips

Attachment: Comments:

Inspection verified hurricane clips fastened with a minimum of three

nails.

5. Roof Geometry: Other Roof

Comments: Inspection verified a gable roof shape.

6. SWR: Yes

Comments: SWR was verified at time of inspection. The Secondary Water

Resistance verified is a self-adhering peel and stick.

7. Opening Protection: None or Some Glazed Openings

Comments: Inspection verified some impact rated opening protection. Not all

glazed openings were protected with impact resistant coverings.

Address Verification



Exterior Elevation



Roof Construction



Roof Construction



Roof Construction



Roof Construction



SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 2101 Sunset Point Rd, Units 2401-2402

FPAT File #MUD2015282

Roof Construction



Uniform Mitigation Verification Inspection Form

Maintain a copy	v of this form and	any documentation i	provided with the insurance	policy

Inspection Date: 11-25-2020					
Owner Information					
Owner Name: Raintree Village Condomin	Contact Person: Robert Kelly				
Address: 2101 Sunset Point Rd, Units 2401-2402		Home Phone:			
City: Clearwater	Zip: 33765	Work Phone: (727) 726-8000			
County: Pinellas	ounty: Pinellas Cell Phone:				
Insurance Company:		Policy #:			
Year of Home: 1973	# of Stories: 1	Email:			

NOTE: Any documentation used in accompany this form. At least one p though 7. The insurer may ask additional content of the co	hotograph must ac	company this form	to validate each attribute n	narked in questions 3
 Building Code: Was the structure the HVHZ (Miami-Dade or Browar A. Built in compliance with the FBO 3/1/2002: Building Permit App B. For the HVHZ Only: Built in corprovide a permit application with [X] C. Unknown or does not meet the 	rd counties), South FC: Year Built . For lication Date (MM/DD/npliance with the SF th a date after 9/1/19	Florida Building Coo homes built in 2002 YYYY) FBC-94: Year Built 994: Building Permi	de (SFBC-94)? /2003 provide a permit applic For homes built in 1	ation with a date after 994, 1995, and 1996
 Roof Covering: Select all roof cov OR Year of Original Installation/Ro covering identified. 				
2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	Provided for Compliance
[X] 1. Asphalt/Fiberglass Shingle [] 2. Concrete/Clay Tile [] 3. Metal [] 4. Built Up [] 5. Membrane [] 6. Other	07-23-2020			0 0 0 0 0
 [X] A. All roof coverings listed above installation OR have a roofing [] B. All roof coverings have a Miami permit application after 9/1/19 [] C. One or more roof coverings do roof coverings meet the requirements. 	permit application Dade Product Appl 1994 and before 3/1/2 not meet the requirer	date on or after 3/1/4 roval listing current 002 OR the roof is onents of Answer "A	02 OR the roof is original and at time of installation OR (for original and built in 1997 or la	built in 2004 or later. the HVHZ only) a roofing
3. Roof Deck Attachment: What is the A. Plywood/Oriented strand board staples or 6d nails spaced at 6" a	(OSB) roof sheathir	ng attached to the ro	of truss/rafter (spaced a maxi	

- [] A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [X] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 2401-2402, Clearwater

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

182 psf.	
	d Concrete Roof Deck.
[] E. Other:	
F. Unknown	or unidentified.
[] G. No attic a	ccess.
5 feet of the	Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within inside or outside corner of the roof in determination of WEAKEST type)
[] A. Toe Nails	
	[] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or [] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
Minimal con	[X]Secured to truss/rafter with a minimum of three (3) nails, and [X]Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from
	the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe
IVI D. CII	corrosion.
[X] B. Clips	[V] Matal accordance that do not according to the town of the two closes on
	[X] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
[] C. Single Wr	
	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
[] D. Double W	•
	[] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
[] E. Structural	[] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. Anchor bolts structurally connected or reinforced concrete roof.
[] F. Other:	
[] G. Unknown	
[] H. No attic a	ccess
	etry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of eture over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[] A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.
[] B. Flat Roof	Total length of non-hip features: ; Total roof system perimeter: Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
[X] C. Other Ro	
[X] A. SWR (a sheathin	<u>Vater Resistance (SWR)</u> : (standard underlayments or hot-mopped felts do not qualify as an SWR) lso called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the ng or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling polymer introvious in the quant of roof covering loss.
[] B. No SWR.	ater intrusion in the event of roof covering loss.
	or undetermined.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 2401-2402, Clearwater

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart		Glazed Openings			Non-Glazed Openings		
openi form	an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		Х	Х	Х		
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	Χ				Χ	Χ

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115
 - [] A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
 - ☐ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
 - [] A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- [] <u>B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only)</u> All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - □ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 □ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 - ☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
- [] <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
 - ☐ C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
 - ☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
 - C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 2401-2402, Clearwater

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FPAT File #MUD2015282

[] <u>N. I</u>	protective coverings not meeting the requirements of "B" with no documentation of compliance (Level N	f Answer "A", "B", or C" o			
	N.1 All Non-Glazed openings classified as Level A, B, C, o	,	on Clared amonings arist		
	N.2 One or More Non-Glazed openings classified as Level I table above		* *		
П	N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above			
[X] <u>X.</u>	None or Some Glazed Openings One or more Glazed		vel X in the table above.		
	MITIGATION INSPECTIONS MUST E Section 627.711(2), Florida Statutes, prov				
Quali	fied Inspector Name: John Felten	License Type: CBC	License or Certificate #: CBC1255984		
Inspe	ction Company: Felten Property Assessment Team	1	Phone: 866-568-7853		
Quali	ied Inspector – I hold an active license as a	: (check one)			
	me inspector licensed under Section 468.8314, Florida Statute ning approved by the Construction Industry Licensing Board				
	lding code inspector certified under Section 468.607, Florida neral, building or residential contractor licensed under Section				
□ Pro	fessional engineer licensed under Section 471.015, Florida St	atutes.			
□ Pro	fessional architect licensed under Section 481.213, Florida St	atutes.			
	y other individual or entity recognized by the insurer as posse fication form pursuant to Section 627.711(2), Florida Statute.		ns to properly complete a uniform mitigation		
License experie	Section 471.015, Florida Statues, must inspect the structure state of the state of	ect employee who possesse I personally performed the	s the requisite skill, knowledge, and e inspection or (licensed		
Qualifi	ed Inspector Signature:Dat	re: <u>11-25-2020</u>			
is subjectifie	ividual or entity who knowingly or through gross need to investigation by the Florida Division of Insurantiate licensing agency or to criminal prosecution. (See this form shall be directly liable for the misconducined the inspection.	nce Fraud and may be sub ection 627.711(4)-(7), Flor	ject to administrative action by the ida Statutes) The Qualified Inspector who		
	eowner to complete: I certify that the named Qualification ce identified on this form and that proof of identification.				
Signa	lignature: Date:				
obtair	dividual or entity who knowingly provides or utters n or receive a discount on an insurance premium to v meanor of the first degree. (Section 627.711(7), Flor	which the individual or en			
The defin	nitions on this form are for inspection purposes only and cannot bees.	oe used to certify any product or	construction feature as offering protection from		

Inspectors Initials Property Address 2101 Sunset Point Rd, Units 2401-2402, Clearwater

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155